

X11e Anywhere Network Node

The Smart Choice of PtP Bridge

Cost-efficient | Optimal Network Capacity | Ultra-high Reliable



X11e Anywhere Network Node (A-NN) is a high-performance single 5 GHz radio wireless backhaul unit designed for last mile extension and cost efficient PtP link deployment. It can be working together with other multiple radios backhaul unit to build a daisy chain or a mesh network. X11e also supports flexible choice of external antenna which can be used for PtP or PtMP connection!

Main Features

- 1 x 5 GHz
- External antenna
- PtP and PtMP
- 400 Mbps real data throughput
- 20/40/80 MHz channel
- IP 67 weatherproof 6kV surge protection

Main Benefits and Applications

- **Optimal Network Capacity** Guaranteed network performance of true throughput and data transmission speed as the entire link's capacity is fully reserved between the two network points.
- **Enhanced Reliability and Security** single radio in one network path enabling maximum data transmission from both ends.
- **Effective Internet Connectivity** Extended network coverage by easy-to-deploy PtP link enabling instant internet access in remote/temporary areas
- **Constant Communication with Excellent Transmission Output** best suit for data transmission in audiovisual form such as video and audio conferencing, for high quality output.
- **Ultra-rapid deployment** PtP connection could be set up in an hour (a day)
- **Cost Efficient PtP Networking** significantly save money and time comparing to costly fibre deployment and maintenance

Best for one-way critical-mission applications demanding high-speed massive data transmission, such as live and recorded video via CCTV feeds, agricultural data analytics, ...etc

Deployment Architecture



X11e Anywhere Network Node

Specifications

Wireless		
Operating Frequency ¹	5.150 - 5.350 GHz 5.470 - 5.850 GHz	
Modulation	OFDM: BPSK, QPSK,16QAM, 64QAM,256QAM DSSS: DBPSK, DQPSK, CCK	
No. of Spatial Stream	2×2: 2 MIMO	
Channel Bandwidth	20/40/80 MHz Channel	
Data Rate	173 Mbps (20MHz); 400 Mbps (40 MHz); 867 Mbps (80 MHz)	
Receive Sensitivity	-91 dBm (20 MHz); -88 dBm (40 MHz); -85 dBm (80 MHz)	
Transmit Power	27 dBm (Max)	
Features	Spectrum Scan, Antenna Alignment	
Antenna		
Connected To	Radio 0	Radio 1
Type	n/a	External 5 GHz
		Optional Antennas: 5 GHz 19 dBi Panel; More Options on Request
Network		
Topology	Point-to-Point (PtP), Point-to-Multipoint (PtMP), Daisy-chain and Ring	
Redundancy	Flow-based Routing, Multiple Drop-off Point, Bonded Link	
Mobility	Mobile Mode	
Path Selection	Bandwidth-based Metrics Load Balancing, Traffic Load Aware Load Balancing	
Traffic Optimization	BUM Traffic Management	
Features	End-to-End Layer 2 Transparent, VLAN 802.11Q Pass-through, Node Recovery	
Security		
Link Encryption	128-bit AES	
Client MAC Access Control	Whitelist ² , Blacklist	
Neighbor MAC Access Control	Whitelist, Blacklist	

Management	
User Interface	Anywhere Node Manager (A-NM) for A-OS
Support	Remote Firmware Upgrade, Network Time Sync, SNMP v1/v2c ² , MIB support ²
Hardware	
No. of Radio	1x5 GHz Radio
Network Interface	1xGE & PoE Port
LED	RUN; LAN; RADIO 0; RADIO 1
Power Supply	802.3at PoE Injector
Power Consumption	25 W (Max.)
Antenna Movement	±30° Up/Down-tilt
MTBF	350,000 hours (50 °C)
Physical Characteristics	
Dimensions	270 × 270 × 80 mm (w/o Mounting)
Weight	1.86 kg (Net w/o Mounting); 2.39 kg (Net w/ Mounting); 2.66 kg (Gross)
Mounting	Pole Mounting (ø40 to ø52 mm)
Environmental	
Temperature	-40 °C to 65 °C (Operating)
Humidity	5% to 95 % Non-condensing
Elevations	86 to 106 kPa
Wind Loading	256 km/h (Max.)
Weatherproof	IP67, 6 kV Common Mode Surge Protection
Certification	
FCC, RCM, KC	
Standard Warranty	
First year free limited hardware warranty and firmware upgrade. The 1/3/5-year extended warranties are available under specific purchase terms and conditions.	
Ordering Information	
Part Number	GE.AP-X11E-00
Description	X11e Anywhere Network Node

¹operating frequency, transmit power and channel bandwidth vary by country/region settings

²available in the future updates

Anywhere Networks is a brand name owned by P2 Mobile Technologies Limited. P2 Mobile Technologies Limited reserves the rights to change, modify, transfer or otherwise revise the publication and the product specification without notice. All scaling metrics outlined in this document are maximum supported values. The scale may vary depending on the deployment scenario and features enabled. Visit www.anywherenetworks.com or contact sales@anywherenetworks.com for more details.